





# Ideal 20

Ideal is a LED exit light that combines cutting edge technology with modern and elegant design. Profile is ideal to use in office spaces, meeting rooms, hospitals, markets and similar environments where the look matters most. Wide range of mounting options, including wall, ceiling and recessed allows for a consistent look and feel across different areas of building.

Viewing distance: ..... < 20 m  
 Light source: ..... LED  
 IP Class: ..... IP43  
 Supply voltage model A: ..... 24 V AC/DC  
 Supply voltage model B: ..... 230 V AC/DC  
 Supply voltage C/AT: ..... 230 V AC  
 Protection class model A: ..... III  
 Protection class model B and C/AT: ..... I  
 Input power model A: ..... < 3 W  
 Input power model B and C/AT: ..... < 5 W / 6 VA  
 Temperature range: ..... -30...+50°C  
 -For models with battery: ..... -10...+40°C  
 Battery / Backup time NI-MH: ..... Ni-MH 6 V / 3 h  
 Body material: ..... Anodized aluminium  
 -Sign: ..... Acrylic  
 -Endpiece: ..... Polycarbonate  
 Mounting options: ..... Surface, recess  
 Country of origin: ..... Finland  
 Warranty: ..... 2 years  
 Standards: ..... EN 60598-2-22, EN 1838, EN ISO:7010



WIKROLUX

## IDEAL 20

Product code	Name	Sign	Supply voltage	Electrical code (STK)
1006000	IDEAL 20 A	E1 24V	AC/DC	4214420
1006002	IDEAL 20 A	E2 24V	AC/DC	4214422
1006003	IDEAL 20 A	E3 24V	AC/DC	4214424
1006001	IDEAL 20 A	E1/E2	24V AC/DC	4214426
1006004	IDEAL 20 A	E3/E3	24V AC/DC	4214428
1006010	IDEAL 20 B	E1	230V AC/DC	4214430
1006012	IDEAL 20 B	E2	230V AC/DC	4214432
1006013	IDEAL 20 B	E3	230V AC/DC	4214434
1006011	IDEAL 20 B	E1/E2	230V AC/DC	4214436
1006014	IDEAL 20 B	E3/E3	230V AC/DC	4214438
1006020	IDEAL 20 C/AT	E1	230V AC	4214440
1006022	IDEAL 20 C/AT	E2	230V AC	4214442
1006023	IDEAL 20 C/AT	E3	230V AC	4214444
1006021	IDEAL 20 C/AT	E1/E2	230V AC	4214446
1006024	IDEAL 20 C/AT	E3/E3	230V AC	4214448

## IDEAL 20 CG-S

Product code	Name	Sign	Supply voltage
1000910	IDEAL 20 B CG-S	E1	230V AC/DC
1000911	IDEAL 20 B CG-S	E2	230V AC/DC
1000912	IDEAL 20 B CG-S	E3	230V AC/DC
1000913	IDEAL 20 B CG-S	E1/E2	230V AC/DC
1000914	IDEAL 20 B CG-S	E3/E3	230V AC/DC

## IDEAL 20 CG-S Ready

Product code	Name	Sign
1000925	IDEAL 20 CG-S Ready	E1
1000926	IDEAL 20 CG-S Ready	E2
1000927	IDEAL 20 CG-S Ready	E3
1000928	IDEAL 20 CG-S Ready	E1/E2
1000929	IDEAL 20 CG-S Ready	E3/E3

## IDEAL 20 Dali

Product code	Name	Sign	Supply voltage
1000471	IDEAL 20 B DALI	E1	230V AC/DC
1000472	IDEAL 20 B DALI	E2	230V AC/DC
1000473	IDEAL 20 B DALI	E3	230V AC/DC
1000474	IDEAL 20 B DALI	E1/E2	230V AC/DC
1000475	IDEAL 20 B DALI	E3/E3	230V AC/DC
1000460	IDEAL 20 C/AT DALI	E1	230V AC
1000465	IDEAL 20 C/AT DALI	E2	230V AC
1000455	IDEAL 20 C/AT DALI	E3	230V AC
1000450	IDEAL 20 C/AT DALI	E1/E2	230V AC
1000451	IDEAL 20 C/AT DALI	E3/E3	230V AC

## IDEAL 20 PLANSAFE Ready

Product code	Name
1800055	IDEAL 20 A
1811015	IDEAL 20 B



## Installation- and spare parts

Product code	Name	Electrical code (STK)
1005740	Battery Ni-MH 6V	8778090
1005760	LED Driver B	
1005765	LED Driver + Charger C/AT	
1005305	LED Unit A, 4/31x230-RE 24V	
1005355	LED Unit B,C 4x230-RE 350mA	
1005902	Protective Mesh Cage 280x280x110 mm	
1005705	Flag Bracket	
1222030	Handle Bracket (Standard)	
1005692	Recess mounting frame / Decorative plate model A and B	
1005696	Recess mounting frame / Decorative plate model C/AT	
1005681	Recess mounting frame / Decorative plate	

